



DESCRIPTION

- 7/8" Air Dielectric Cable (SDY-50-22)
- Standard Q/12JD 6350-2020
- Corrugated Copper
- Low Attenuation
- Low VSWR
- High Power Rating

ELECTRICAL DATA

IMPEDANCE		50±1 Ω
VELOCITY OF PROPAGATION		93%
MAXIMUM FREQUENCY		3 GHz
PEAK POWER RATING		72.9 kW
DC BREAKDOWN VOLTAGE		2.7 kV
DC RESISTANCE	Inner conductor	0.75 Ω/km
	Outer conductor	0.75 Ω/km
CAPACITANCE		71 pF/m
VSWR	AM 550 kHz - 1600 kHz	≤1.06
	FM 87 MHz - 108 MHz	≤1.08
	DAB 170 MHz - 240 MHz	≤1.10
	UHF 470 MHz - 870 MHz	≤1.10

Contact us for premium value in your specific frequency band.

MECHANICAL DATA

INNER CONDUCTOR	Smooth copper tube	9.3 mm
DIELECTRIC	PE strip	20.8 mm
OUTER CONDUCTOR	Corrugated copper tube	25.2 mm
OUTER JACKET	PE	29.0 mm
WEIGHT		786 kg/km
MIN. BENDING RADIUS (single)		90 mm
MIN. BENDING RADIUS (multiple)		300 mm
NUMBER OF BENDS (minimum)		15
OPERATING TEMPERATURE		-45°C+85°C
INSTALLATION TEMPERATURE		-40°C+60°C

ATTENUATION AND AVERAGE POWER

FREQUENCY (MHz)	ATTENUATION (dB/100 m)	AVERAGE POWER (kW)
22	0,16	61
88	1,10	9
100	1,18	8,3
108	1,23	8
174	1,57	6
200	1,69	5
450	2,50	4
500	2,70	3,5
600	3,00	3
700	3,20	2,7
800	3,50	2,5

Attenuation at 20°C (68°F) cable temperature, maximum value shall be 105% of the nominal attenuation value.

Average power rating at 40°C (104°F) ambient temperature.

Cable manufactured by ASCEND



ALDENA is the official distributor and European warehouse
of Tianjin Zhonghuan Ascend Technologies Co., Ltd (ASCEND)

Specification are subject to change without notice

TELECOMUNICAZIONI ALDEN A SRL

www.aldena.it - aldena@aldena.it