

ELECTRICAL FEATURES

WORKING BAND: UHF
BANDWIDTH: 470 ÷ 1200 MHz
AVERAGE GAIN: 4 dBd (6.2 dBi)
IMPEDANCE: 50 Ohm
ANTENNA FACTOR: 10 ÷ 26
POLARIZATION: vertical (o horizontal)
CONNECTOR: N female

MECHANICAL FEATURES

MATERIALS: elements and body in aluminium,
PVC bracket, teflon isolators
MOUNTING: directly on mast Ø 20 mm
MOUNTING BRACKETS: included
TREATMENTS: painted elements and body
AVAILABLE VERSIONS AND CODE:
ALP1107710 – typical calibration report
ALP1107710SIT – individual calibration certificate
ANTENNA DIMENSIONS: 875x326x150mm
WEIGHT: 1.7 Kg net
PACKING: aluminium case included

RECCOMENDED ACCESSORIES

XTRKIT: aluminum tripod estensibile, up to 4mt,
with nylon mast Ø 20mm 1mt length
CVLMR2000102/7:
LMR200 cable with attenuation data N male ÷ BNC male

ALP11 07 710

VHF/UHF
Accessories

MEASUREMENT ANTENNA

Antenna log-periodica a 11 elementi
in alluminio verniciato.
Adatta per misure da 470 a 1200 MHz

*Log-periodic antenna 11 elements
on painted aluminium.
Suitable for measurement from 470 to 1200 MHz.*

